		Your pa	artner:		Edscha Trailer Systems
EN					Stand 09/201
Enquiry			Reference r	no. (Customer)	
Customer no.:			Order a	address:	
Customer:					
Contact person:			Deliver	y address:	
Telephone: E-mail:			Reques	sted delivery date:	
Edada Tualla		Doof Tone			
Edscha Traile CurtainSider Roof	_	коот туре		Tarpaulin Roofs	Full Tarpaulin Roof
Standard	Volume	Universal	Universal Classic		
☐ CS-Hybrid ☐ CS-ECO	☐ CS-Hybrid ☐ CS-ECO	☐ CS-Profi☐ CS-Hybrid☐ CS-ECO	☐ CS-Profi☐ CS-Hybrid☐ CS-ECO	☐ Compact	□ VP-Profi □ VP-Standard □ VP-ECO
Construction parameter Standard width 2550 mm (mounted with panel) Adjustable width until max. 2550 mm (mounted with panel) mm Cunstruction width:				Height TailWing	Upper edge of roof C Upper edge of loading sideboards C = mm
width of 2600 n for adjusting on Construction kit	nm with panel-h yourself not mounted w nm with panel-h	ithout panel until eight 400 - 900 m ithout panel until eight 901 - 1200 r			

European Trailer Systems GmbH

for adjusting on yourself